



规格说明 MACHINE SPECIFICATIONS

型号 MODEL	Super-NJ 212	
针数 GAUGE	7G/10G/12G/14G	
编织宽度 KNITTING WIDTH	48英寸 48-INCH	
编织速度 KNITTING SPEED	最高1.3米/秒 MAX.1.3M/SEC	
编织系统 KNITTING SYSTEM	双系统-单头 DOUBLE SYSTEM, SINGLE CARRIAGE	
线圈密度 STITCH LENGTH	步进马达控制, 24组密度选择 STEPPING MOTOR CONTROL, 24 GROUP STITCH FOR CHOICE	
移床 RACKING	由伺服电机控制, 行程2英寸 CONTROLLED BY SERVO MOTOR MAX 2-INCH	
沉降片 SINKER SYSTEM	程式3工位系统 PROGRAMMABLE 3-WAY SINKER SYSTEM	
选针 NEEDLE SELECTION	由选针器作全提花选针 FULL JACQUARD SELECTION BY ACTUATORS	
卷布罗拉 TAKE DOWN ROLLER	高位罗拉系统 UPPER ROLLER SYSTEM	
纱咀 YARN CARRIERS	16个 16 PCS	
天线架 TOP TENSIONS	17个 17 PCS	
自停装置 STOP MOTION	断纱、结头、断针、摆动、数据错误等 YARN BREAKAGE, KNOT/NEEDLE BREAKAGE, DATA ERROR, ETC.	
传动机构 DRIVE SYSTEM	伺服系统传动机构 AC SERVO SYSTEM	
选胸 OPTION	储纱器 YARN STORAGES 主罗拉 MAIN ROLLER	
控制系统 CONTROLLER		
系统 SYSTEM	预设程序系统 STORED PROGRAM SYSTEM	
数据输入 DATA INPUT	USB	
显示 CONTROL DISPLAY	彩色液晶触摸屏 FULL COLOR LCD TOUCHABLE DISPLAY	
电源 POWER	单相 2.5KW AC220V SINGLE PHASE	

* 内容如有改变, 恕不通知。 Specification and design are subject to be changed without notice due to improvement of the machine.

MATSUYA
KNIT TO THE FUTURE

MATSUYA INDUSTRIES LTD.

26-7, 1-Chome, Mikawa-Ajiro-Honnachi, Ajiro,

Aichi 446-0059 Japan

Tel : 81-566-71-5188

Fax: 81-566-72-7820

E-Mail: info@matsuya-corp.com

松谷机械(惠州)有限公司

MATSUYA MACHINERY (HUI ZHOU) CO.,LTD.

中国广东省惠州市惠城区仲恺大道(惠环)188号

No.188 Zhong Kai Road, Hui Huan, Hui Cheng District,

Huizhou City, Guangdong, P.R.C

电话 (Tel) : 86-752-2662868

传真 (Fax): 86-752-2663588

邮编 (P.C): 516008

电邮 (E-Mail): sale@matsuya.com.cn

网址 (Website): www.matsuya.com.cn



Super-NJ 212

电脑提花横编织机 (毛衫/帽子/钱包/鞋面等)

Computerized Jacquard Flat Knitting Machine

(Sweater / Muslim Cap/Wallet/Shoe-Cover etc.)

MATSUYA

KNIT TO THE FUTURE

2014.03